ELKATHERM®

Power of comfort

Specifications of seasonal space heating energy efficiency from the Commission Regulation (EU) 2015/1188

Model designations: Electric panel storage heater PLD125, Digital radio thermostat 712, Surface mount receiver 714 or Wireless wall socket receiver 713, Router 701UK

Details	Symbol	Value	Unit
Heat output			
Nominal heat output	P_{nom}	1.3	kW
Minimum heat output (guide value)	P_{min}	1.3	kW
Maximum continuous heat output	$P_{max,c}$	1.3	kW
Auxiliary power consumption			
At nominal heat output	el_{max}	0.000	kW
At minimum heat output	el_{min}	0.000	kW
In standby mode	el_{SB}	0.000	kW

Type of heat output / room temperature control (please select one option)		
Room temperature control with mechanical thermostat	☐ yes	☐ no
with electronic room temperature control	☐ yes	☐ no
With electronic room temperature control and time control	☐ yes	☐ no
electronic room temperature control and weekday control	☒ yes	☐ no

Other control options (multiple answers possible)		
Room temperature control with presence detection	☐ yes	☒ no
Room temperature control with open window detection	☐ yes	☒ no
With remote control option	☒ yes	☐ no
With adaptive control of start of heating	☐ yes	☒ no

Contact details	
Company	ELKATHERM GmbH & Co. KG
Street/No.	Im Heidchen 6-8
Postcode/Place	56424 Mogendorf
Country	Germany